

GRAFFITI REMOVERS & COMMERCIAL CLEANERS

**ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE**

**EnviroPenetrator™ Biodegradable Graffiti Remover****PRODUCT DESCRIPTION:**

TRIVCOR EnviroPenetrator™ Graffiti Remover is a biodegradable, water based, environmentally friendly graffiti remover designed to work as a stand alone graffiti remover for spray paint or ink based graffiti or as a penetrator application in our 3 step removal process in conjunction with our EnviroPeel™ Graffiti Remover.

For surfaces with light to heavy graffiti applications, EnviroPenetrator™ is liberally applied to the surface and allowed to dwell prior to the application of Enviro-Peel™. This 3 step process is specifically designed for the removal of graffiti from porous surfaces such as brick, concrete, natural stone or sandstone.

APPLICATION:**NON-POROUS SURFACES**

On previously painted surfaces, plastic, polished metal, stainless steel, aluminum or any other type non-porous surface, apply EnviroPenetrator™ Graffiti Remover directly to the surface or to a rag and then wipe the surface with the rag. On painted surfaces, remove graffiti in small sections to ensure that the EnviroPenetrator™ graffiti remover does not attack the surface. In the case where the graffiti remover dissolves the underlying paint, immediately neutralize the cleaned area with water. Use a clean section of the rag to remove any remaining graffiti residue once the majority of the graffiti has been removed. Always wash the surface with water to neutralize the graffiti remover when completed the job.

If EnviroPenetrator™ will not remove the graffiti, try our PVC™ Graffiti Remover for sensitive surfaces or EGR Pro™ as it is designed to work as a stand alone product for removing graffiti, pen, marker or ink in a single step.

Porous Surfaces: (Brick or Concrete)**Three Step Process****Step 1.**

For brick or concrete surfaces, use a stiff brush to apply the EnviroPenetrator™ graffiti remover into the pores of the surface. Apply the product liberally and work the product into the pores using a twisting motion of the brush. Allow the product to dwell in the pores for a minimum of 15-20 minutes.

Step 2.

Once the EnviroPenetrator™ has been allowed to dwell for the recommended time, brush apply a liberal coat of Enviro-Peel™ on top of the pretreated surface. Allow the EnviroPeel™ to dwell for a minimum of 20 minutes. After the allotted dwell time, test a small area with a rag or stiff brush to determine if product is ready to be removed. If the white gel EnviroPeel™ is picking up graffiti pigment, you may then begin pressure washing process.

Step 3.

You may use high pressure water to wash the surface of the graffiti. If a pressure washer is not available, we recommend washing (scrubbing) the treated surface with warm water and an industrial grade degreaser or soap. Rinse with fresh water when finished.

(DO NOT SET PRESSURE ON WASHER TOO HIGH THAT IT MAY DAMAGE THE SURFACE OF THE SUBSTRATE. IF 100% OF THE GRAFFITI IS NOT REMOVED IN FIRST ATTEMPT, THEN PERFORM A SECOND APPLICATION WHEN BRICK IS DRY. WE RECOMMEND ROOM TEMPERATURE TO LUKE WARM WATER (21°C-65°C / 70°F-150°F) HOT WATER OR STEAM MAY DAMAGE THE SURFACE OR GROUTED AREAS.)

GRAFFITI REMOVERS & COMMERCIAL CLEANERS



ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE



EnviroPenetrator™ Biodegradable Graffiti Remover

APPLICATION (CONTINUED)

Multiple applications may be required depending on the substrate and the graffiti.

Sandstone or Poor Concrete Surfaces

Step 1.

For Sandstone or poor concrete surfaces, use a brush to apply the EnviroPenetrator™ graffiti remover into the pores of the surface. Apply the product liberally and work the product into the pores using a twisting motion of the brush. Allow the product to dwell in the pores for a minimum of 15 minutes and then test to see if graffiti is dissolving.

Step 2.

Once the EnviroPenetrator™ has been allowed to dwell for the recommended time, brush apply a liberal coat of EnviroPeel™ on top of the pretreated surface. Allow the EnviroPeel™ to dwell for a minimum of 20 minutes. After the allotted dwell time, test a small area with a rag or stiff brush to determine if product is ready to be removed. If the white gel EnviroPeel™ is picking up graffiti pigment, you may then begin the washing process.

Step 3.

DO NOT USE HIGH PRESSURE WATER TO REMOVE GRAFFITI FROM THE SURFACE. SANDSTONE IS EXTREMELY SOFT AND WILL BE DAMAGED BY HIGH PRESSURE WATER.

We recommend washing (scrubbing) the treated surface with warm water and an industrial grade degreaser or soap. Rinse with fresh water when finished. If shadows remain, perform a second removal procedure.

MIXING

DO NOT DILUTE. TRIVCOR EnviroPenetrator Graffiti Remover is 100% biodegradable and soluble in water. Once graffiti removal is complete, the surface should be thoroughly washed down with water to neutralize any remaining active product.

COVERAGE

Coverage of the remover will vary depending on how heavy the graffiti is painted on the surface. Multiple applications may be required to completely remove graffiti. Allowing proper dwell times will maximize the coverage of the remover.

STORAGE AND HANDLING

TRIVCOR Enviro-Penetrator™ Graffiti Remover is Non-Hazardous.

Shipping Information:

3.78 Litres (1 US Gallon) F Style
Approximate Shipping Weight: 5 kg (11 lbs)
18.9 Litres (5 US Gallons) Pail
Approximate Shipping Weight: 24.97 kg (55 lbs)

GRAFFITI REMOVERS & COMMERCIAL CLEANERS**ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE****EnviroPenetrator™ Biodegradable Graffiti Remover****STORAGE AND HANDLING (CONTINUED)**

Storage: Keep the Graffiti Remover products in a sealed container and store in a cool, dry, well ventilated storage in compliance with all current and local regulations. Keep out of direct sunlight, moisture or rain. Maintain material in sealed containers at all times. Do not store materials in unlabelled containers.

Shelf Life: The expected shelf life of TRIVCOR Graffiti Products is 24 months from the date of manufacture if stored as indicated above, in unopened and sealed containers. Liquid products should be agitated before use if it has been stored for an extended period.

PRECAUTIONS:

Please refer to the Material Safety Data Sheet for proper safe handling procedures. Always wear proper protective gear such as Nitril gloves and safety glasses that have a protective splash guard or goggles. Always wash any area where product may have come in contact with your hands or skin and launder any clothing worn during product use.

Limitation of Remedies:

TRIVCOR Enviro Limited makes no express warranty implied or otherwise with respect to this product and expressly disclaims liability for consequential or incidental damages. Buyer's sole remedy shall be refund or replacement of products purchased at the discretion of the distributor or TRIVCOR affiliates.