

GRAFFITI REMOVERS & COMMERCIAL CLEANERS

**ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE**



EnviroPeel™ Environmentally Friendly Paint Stripper

PRODUCT DESCRIPTION:

TRIVCOR EnviroPeel™ Paint Stripper and Graffiti Remover is a biodegradable, environmentally friendly paint stripper and graffiti remover designed specifically to replace harsh methylene chloride based paint strippers. The unique formulation of EnviroPeel™ makes it suitable for a variety of applications such as stripping paint from wood surfaces, aerospace components, automotive parts and more.

EnviroPeel™ is also used in conjunction with EnviroPenetrator™ in our unique 3 step process to remove graffiti from porous surfaces such as brick, concrete or sandstone.

APPLICATION:

Paint Stripping

EnviroPeel™ is extremely easy to use. Simply apply the product to the surface liberally using a brush or roller and allow to dwell for an extended period. Dwell times for urethane and epoxy based paints are typically 1 hour. The paint on the surface should begin to wrinkle and peel away from the substrate. Simply use a scraper, wire brush or steel wool to remove paint from the treated area. Multiple applications may be required depending on the thickness and type of paint being removed.

For larger surface areas, the EnviroPeel™ may be applied using an airless spray system.

TIP: To strip heavily painted areas, apply the EnviroPeel to the surface and then apply a thin sheet of plastic wrap over the area and allow to dwell for an extended period of time. This will allow the stripper to break down the paint through the layers while keeping the area from drying out. This is especially useful when stripping layers of paint from wood surfaces such as door frames, window frames, cabinets and more.

We recommend testing a small area prior to using EnviroPeel™.

Graffiti Removal

Non-Porous Surfaces

EnviroPeel™ may be used by itself or in conjunction with EnviroPenetrator™ to remove heavy graffiti from porous surface.

Multi-layered Graffiti Tags

For heavy graffiti on brick, cinder block or any type porous surfaces, apply the EnviroPeel™ liberally and allow to dwell for an extended period. (up to one hour depending on the thickness of the graffiti tag) Once the dwell time has passed, test a small area to determine how easily the graffiti is removed. Use a pressure washer with room temperature or warm water (21°C-65°C / 70°F-150°F) to remove the majority of the graffiti from the surface. If the surface is exposed after washing and shadowing remains, use the EnviroPenetrator™ and EnviroPeel™ three step process to remove the final remnants of graffiti remaining including any shadows.

Continued on page 2

GRAFFITI REMOVERS & COMMERCIAL CLEANERS



ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE



EnviroPeel™ Environmentally Friendly Paint Stripper

Porous Surfaces: (Brick or Concrete)
Three Step Process

Step 1. - EnviroPenetrator Application

For brick or concrete surfaces, use a stiff brush to apply the EnviroPenetrator™ graffiti remover into the pores of the surface. Apply the product liberally and work the product into the pores using a twisting motion of the brush. Allow the product to dwell in the pores for a minimum of 10-15 minutes.

Step 2. - EnviroPeel Application

Once the EnviroPenetrator™ has been allowed to dwell for the recommended time, brush apply a liberal coat of EnviroPeel™ on top of the pretreated surface. Allow the EnviroPeel™ to dwell for a minimum of 20 minutes. After the allotted dwell time, test a small area with a rag or stiff brush to determine if product is ready to be removed. If the white gel EnviroPeel™ is picking up graffiti pigment, you may then begin pressure washing process.

Step 3. - Pressure Washing

You may use high pressure water to wash the surface of the graffiti. If a pressure washer is not available, we recommend washing (scrubbing) the treated surface with warm water and an industrial grade degreaser or soap. Rinse with fresh water when finished.

(DO NOT SET PRESSURE ON WASHER TOO HIGH THAT IT MAY DAMAGE THE SURFACE OF THE SUBSTRATE. IF 100% OF THE GRAFFITI IS NOT REMOVED IN FIRST ATTEMPT, THEN PERFORM A SECOND APPLICATION WHEN BRICK IS DRY. WE RECOMMEND ROOM TEMPERATURE TO WARM WATER (21°C-65°C / 70°F-150°F) HOT WATER OR STEAM MAY DAMAGE THE SURFACE OR GROUTED AREAS.)

Soft Brick or Sandstone

For soft brick or sandstone surfaces, use a stiff brush to apply the graffiti remover into the pores of the surface. Apply the product liberally and work the product into the pores using a twisting motion of the brush. Allow the product to dwell in the pores for a minimum of 20-30 minutes and then test to see if graffiti is dissolving.

DO NOT USE HIGH PRESSURE WATER TO REMOVE GRAFFITI FROM THE SURFACE. SANDSTONE IS EXTREMELY SOFT AND WILL BE DAMAGED BY HIGH PRESSURE WATER.

We recommend washing (scrubbing) the treated surface with warm water and an industrial grade degreaser or soap. Rinse with fresh water when finished. If shadows remain, allow surface to dry and perform a second removal procedure.

MIXING

DO NOT DILUTE. TRIVCOR EnviroPeel™ Paint Stripper and Graffiti Remover is 100% biodegradable and soluble in water. Once graffiti removal is complete, the surface should be thoroughly washed down with water to neutralize any remaining active product.

COVERAGE

Coverage of the remover will vary depending on how heavy the graffiti is painted on the surface. Multiple applications may be required to completely remove graffiti. Allowing proper dwell times will maximize the coverage of the remover.

GRAFFITI REMOVERS & COMMERCIAL CLEANERS

**ENVIRONMENTALLY FRIENDLY
BIODEGRADABLE**



EnviroPeel™ Environmentally Friendly Paint Stripper

STORAGE AND HANDLING

TRIVCOR EnviroPeel™ Paint Stripper and Graffiti Remover is Non-Hazardous, Non-Flammable.

Shipping Information: 3.78 Litre (1 US Gallon) F Style
 Approximate Shipping Weight: 5.5 kg (12 lbs)

 18.9 Litre Pail (5 US Gallons)
 Approximate Shipping Weight: 26 kg (58 lbs)

Storage: Keep the Graffiti Remover products in a sealed container and store in a cool, dry, well ventilated storage in compliance with all current and local regulations. Keep out of direct sunlight, moisture or rain. Maintain material in sealed containers at all times. Do not store materials in unlabelled containers.

Shelf Life: The expected shelf life of TRIVCOR Graffiti Products is 24 months from the date of manufacture if stored as indicated above, in unopened and sealed containers. Liquid products should be agitated before use if it has been stored for an extended period.

PRECAUTIONS:

Please refer to the Material Safety Data Sheet for proper safe handling procedures. Always wear proper protective gear such as Nitril gloves and safety glasses that have a protective splash guard or goggles. Always wash any area where product may have come in contact with your hands or skin and launder any clothing worn during product use.

Limitation of Remedies:

TRIVCOR Enviro Limited makes no express warranty implied or otherwise with respect to this product and expressly disclaims liability for consequential or incidental damages. Buyer's sole remedy shall be refund or replacement of products purchased at the discretion of the distributor or TRIVCOR affiliates.